

APPLYING IMPREGNATING OIL AND FINISHING OIL ON UNFINISHED WOOD

WHAT YOU MUST KNOW

1. IMPREGNATING OIL is a natural safe vegetable oil containing resins which acts as a primer to facilitate the crystallization of the oils in the in-depth pores of the wood and non toxic mineral pigments to create the colour (Sahara doesn't contain the pigments)
2. It is available in various colours.
3. FINISHING OIL is a natural vegetable oil containing natural resins that protect the pores of wood on the surface that crystallizes with naturally occurring compounds in the wood and the previously applied IMPREGNATING OIL
4. It must be applied a minimum of 20 - 24 hours after IMPREGNATING OIL
5. Shake/stir each oil very well just before use

-
1. Sand the floor in the direction of the grain with a maximum of 120 grit sandpaper to open the pores of the wood. It is preferable to carry out a test on a small surface (or on the 'back' of a piece) to make sure that the required colour is achieved. A poor sanding job can affect the color and the quality of the completed application.
 2. Ensure that surface to be treated is well sanded and free from dust. The application should be done with a cotton cloth (small areas) or with the SIGNATURE APPLICATOR (large areas)
 3. To avoid accumulations of oil, extend until the oil is completely absorbed by the wood. Remove the excess with a clean cloth. Work in 15-minute sections at a time. Remove the excess of oil with a clean cotton cloth.
 4. Allow to dry 24 hours by preventing any movement and movement of furniture
 5. Apply the FINISHING OIL in thin layer and dry the excess with a clean cotton cloth. Work in 15-minutes sections at a time.
 6. Allow to dry 24 hours by preventing any movement and movement of furniture

**** Note that the OILS are complementary; they must be used together ****

Wait at least 21 days after the oil application to allow the oil to fully cure before beginning regular cleaning and maintenance of your SIGNATURE oiled floor. Prior to this time, wash your floor with lukewarm water only and avoid dragging heavy objects that could damage the surface.