






EXPRESSION
prefinished hardwood floors



GENERAL SPECIFICATIONS

Characteristics	Parquets Alexandra Engineered Lock	
Description	<ul style="list-style-type: none"> • Prefinished engineered floor with locking seal for quick installation 	
Thickness	<ul style="list-style-type: none"> • ± 1/2 in. (12 mm): hardwood veneer of 1/8 inch (3mm) on a 3/8 inch (9mm) plywood 	
Length	<ul style="list-style-type: none"> • Random lengths 12 inches (350 mm) to 78 inches (1.95 m) 	
Widths	<ul style="list-style-type: none"> • 3-7/16 inches (87 mm) and 5-3/16 inches (131 mm) 	
Species	<ul style="list-style-type: none"> • 4 species : Hard Maple, Red Oak, Birch, Walnut 	
Grades	<ul style="list-style-type: none"> • Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots) 	
Colors	<ul style="list-style-type: none"> • 13 colors : Natural, Gunstock, Copper, Cappuccino, Bronze, Latte, Urbain, Eclipse, Baladi, Flamenco, Barley, Tango and Chocolate 	
Finish	<ul style="list-style-type: none"> • Complete finish system that creates a “thicker” finish that is UV cured. • Wear resistance: superior layer finish based on acrylic and polyurethane with nanoparticles that provides a superior resistance to wear. • Scratch resistance: use of aluminium oxide particles and nanoparticles gives Expression better scratch resistance than most products on the market. • Gloss: semi-gloss (50%) and Satin (30%). Gloss levels are more stable over time because of the resin quality and nanoparticles used in our finish. • Environment : no off-gassing of VOC 	
Installation	<ul style="list-style-type: none"> • Floating with an approved underlay/membrane (above grade, on grade or below grade) 	
Subfloor	<ul style="list-style-type: none"> • Wood, concrete or hot water radiant heating systems. 	
Membranes	<ul style="list-style-type: none"> • Finitec : Acousti-Tech™ Premium and Acousti-Tech™ VP 	
Maintenance	<ul style="list-style-type: none"> • With spray cleaner for prefinished floor 	
Use	<ul style="list-style-type: none"> • Commercial or Residential 	
Accessories	<ul style="list-style-type: none"> • Nosings and Reducers (Other accessories available on special order) 	
Warranty	<ul style="list-style-type: none"> • Lifetime structural warranty on manufacturing defects. • Residential: 35 years Finish warranty. • Commercial: 3 years Finish warranty. 	
Packaging	3-7/16 inches (87 mm)	5-3/16 inches (131 mm)
Contents of a box	<ul style="list-style-type: none"> • 34 ft² 	<ul style="list-style-type: none"> • 34 ft²
Dimensions of a box	<ul style="list-style-type: none"> • 78-1/16 in L x 11 in W x 3 in H 	<ul style="list-style-type: none"> • 78-1/16 in L x 11 in W x 3 in H
Weight of a box	<ul style="list-style-type: none"> • 49 to 53 lb 	<ul style="list-style-type: none"> • 49 to 53 lb
Size of a pallet	<ul style="list-style-type: none"> • 40 boxes = 1 360 ft² (4 boxes per Layer x 10 boxes High) 	<ul style="list-style-type: none"> • 40 boxes = 1 360 ft² (4 boxes per Layer x 10 boxes High)
Dimensions of a pallet	<ul style="list-style-type: none"> • 86 in L x 38 in W x 35 in H 	<ul style="list-style-type: none"> • 86 in L x 38 in W x 35 in H
Hardness of species *		
* As per Janka Hardness scale Force applied in pound(Lb)	<ul style="list-style-type: none"> • Red Oak : 1290 Lb  	<ul style="list-style-type: none"> • Birch : 1260 Lb 
	<ul style="list-style-type: none"> • Hard Maple : 1450 Lb  	<ul style="list-style-type: none"> • Walnut : 1010 Lb 