




**SIGNÉ** **A**  
**ALEXANDRA**  
 prefinished hardwood floors



# GENERAL SPECIFICATIONS

Characteristics		Parquets Alexandra Engineered Lock	
Description	<ul style="list-style-type: none"> <li>• Prefinished engineered floor with locking seal for quick installation</li> </ul>		
Thickness	<ul style="list-style-type: none"> <li>• ± 1/2 in. (12 mm): hardwood veneer of 1/8 inch (3mm) on a 3/8 inch (9mm) plywood</li> </ul>		
Length	<ul style="list-style-type: none"> <li>• Random lengths 12 inches (350 mm) to 78 inches (1.95 m)</li> </ul>		
Widths	<ul style="list-style-type: none"> <li>• 3-7/16 inches (87 mm) and 5-3/16 inches (131 mm)</li> </ul>		
Species	<ul style="list-style-type: none"> <li>• 3 species: Hard Maple, Red Oak and Birch</li> </ul>		
Grades	<ul style="list-style-type: none"> <li>• Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots)</li> </ul>		
Colors	<ul style="list-style-type: none"> <li>• 4 colors : Carat, Voilà!, Noble and Rebel</li> </ul>		
Finish	<ul style="list-style-type: none"> <li>• Complete finish system that creates a “thicker” finish that is UV cured.</li> </ul>		
	<ul style="list-style-type: none"> <li>• Wear resistance: superior layer finish based on acrylic and polyurethane with nanoparticles that provides a superior resistance to wear.</li> </ul>		
	<ul style="list-style-type: none"> <li>• Scratch resistance: use of aluminium oxide particles and nanoparticles gives Expression better scratch resistance than most products on the market.</li> </ul>		
	<ul style="list-style-type: none"> <li>• Gloss: Matte (15%). Stable gloss in the time because of the resin quality used and the nanoparticles.</li> </ul>		
	<ul style="list-style-type: none"> <li>• Environment : no off-gassing of VOC</li> </ul>		
Installation	<ul style="list-style-type: none"> <li>• Floating with an approved underlay/membrane (above grade, on grade or below grade)</li> </ul>		
Subfloor	<ul style="list-style-type: none"> <li>• Wood, concrete or hot water radiant heating systems.</li> </ul>		
Membranes	<ul style="list-style-type: none"> <li>• Finitec : Acousti-Tech™ Premium and Acousti-Tech™ VP</li> </ul>		
Maintenance	<ul style="list-style-type: none"> <li>• With spray cleaner for prefinished floor</li> </ul>		
Use	<ul style="list-style-type: none"> <li>• Commercial or Residential</li> </ul>		
Accessories	<ul style="list-style-type: none"> <li>• Nosings and Reducers (Other accessories available on special order)</li> </ul>		
Warranty	<ul style="list-style-type: none"> <li>• Lifetime structural warranty on manufacturing defects.</li> </ul>		
	<ul style="list-style-type: none"> <li>• Residential: 35 years Finish warranty.</li> </ul>		
	<ul style="list-style-type: none"> <li>• Commercial: 3 years Finish warranty.</li> </ul>		
Packaging		3-7/16 inches (87 mm)	5-3/16 inches (131 mm)
Contents of a box	<ul style="list-style-type: none"> <li>• 34 ft<sup>2</sup></li> </ul>		<ul style="list-style-type: none"> <li>• 34 ft<sup>2</sup></li> </ul>
Dimensions of a box	<ul style="list-style-type: none"> <li>• 78-1/16 in L x 11 in W x 3 in H</li> </ul>		<ul style="list-style-type: none"> <li>• 78-1/16 in L x 11 in W x 3 in H</li> </ul>
Weight of a box	<ul style="list-style-type: none"> <li>• 49 to 53 lb</li> </ul>		<ul style="list-style-type: none"> <li>• 49 to 53 lb</li> </ul>
Size of a skid	<ul style="list-style-type: none"> <li>• 40 boxes = 1 360 ft<sup>2</sup> (4 boxes per Layer x 10 boxes High)</li> </ul>		<ul style="list-style-type: none"> <li>• 40 boxes = 1 360 ft<sup>2</sup> (4 boxes per Layer x 10 boxes High)</li> </ul>
Dimensions of a skid	<ul style="list-style-type: none"> <li>• 86 in L x 38 in W x 35 in H</li> </ul>		<ul style="list-style-type: none"> <li>• 86 in L x 38 in W x 35 in H</li> </ul>
Hardness of species *			
* As per Janka Hardness scale Force applied in pound(Lb)	<ul style="list-style-type: none"> <li>• Red Oak : 1290 Lb </li> </ul>		<ul style="list-style-type: none"> <li>• Birch : 1260 Lb </li> </ul>
	<ul style="list-style-type: none"> <li>• Hard Maple : 1450 Lb </li> </ul>		