






GENERAL SPECIFICATIONS

Characteristics	Parquets Alexandra Engineered T-G (Tongue & Groove)	
Description	<ul style="list-style-type: none"> Preoiled Engineered Floor made with hardwood veneer on a 7 layers plywood of Baltic birch 	
Thickness	<ul style="list-style-type: none"> ± 1/2 in. (12 mm): hardwood veneer of 1/8 inch (3mm) on a 3/8 inch (9mm) plywood 	
Length	<ul style="list-style-type: none"> Random lengths 12 inches (350 mm) to 78 inches (1.95 m) 	
Widths	<ul style="list-style-type: none"> 3-1/4 inches (83 mm) and 5-3/16 inches (131 mm) 	
Species	<ul style="list-style-type: none"> 4 species : Hard Maple, Red Oak, Birch, Walnut 	
Grades	<ul style="list-style-type: none"> Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots) 	
Colours	<ul style="list-style-type: none"> 11 colors : Sahara (Except Red Oak), Champagne, Amaretto, Ginger (Hard Maple only), Tan, Truffle, Ardoise, Shadow, Storm, Graphite and Onyx 	
Finish	<ul style="list-style-type: none"> Vegetable oil naturally impregnated into the wood – available coloured or natural. Colour (when chosen) created with natural, non-toxic mineral pigments. Finish mat 5 degree gloss (increases as the floor ages) 100% ecological and biodegradable oil. Zero VOC 	
Installation	<ul style="list-style-type: none"> Nailed, stapled or glued (at all grades) 	
Subfloor	<ul style="list-style-type: none"> Wood, concrete or hot water radiant heating systems. 	
Membranes	<ul style="list-style-type: none"> Finitec : Acousti-Tech™ 7000, 5000, 3500 et Acousti-Tech™ Lead 6, 4.5, 3.3 	
Maintenance	<ul style="list-style-type: none"> Sweep or vacuum regularly to remove dust & grit Damp mop with warm water as needed Wood soap : ideally every week Revitalizer : ideally every 5 washes Regenerating oil : 2-10 years, depending on the wear 	
Use	<ul style="list-style-type: none"> Commercial or Residential 	
Accessories	<ul style="list-style-type: none"> Nosings, Reducers and Vents (Other accessories available on special order) 	
Warranty	<ul style="list-style-type: none"> Lifetime structural warranty on manufacturing defects No finish warranty as the oil is in the wood and becomes part of the structure. Only oil issues relating to a manufacturing defect will be considered for warranty purposes. Parquets Alexandra offers specific maintenance and repair products for our pre-oiled wood and recommends using only these products on our floors. We are not responsible for the use of competitor's products. 	
Packaging	3-1/4 inches (83 mm)	5-3/16 inches (131 mm)
Contents of a box	<ul style="list-style-type: none"> 30 ft² 	<ul style="list-style-type: none"> 34 ft²
Dimensions of a box	<ul style="list-style-type: none"> 78-1/16 in L x 11 in W x 3 in H 	<ul style="list-style-type: none"> 78-1/16 in L x 11 in W x 3 in H
Weight of a box	<ul style="list-style-type: none"> 49 to 53 lb 	<ul style="list-style-type: none"> 49 to 53 lb
Size of a pallet	<ul style="list-style-type: none"> 40 boxes = 1 200 ft² (4 boxes per Layer x 10 boxes High) 	<ul style="list-style-type: none"> 40 boxes = 1 360 ft² (4 boxes per Layer x 10 boxes High)
Dimensions of a pallet	<ul style="list-style-type: none"> 86 in L x 38 in W x 35 in H 	<ul style="list-style-type: none"> 86 in L x 38 in W x 35 in H
Hardness of species *		
* As per Janka Hardness Scale Force applied in pound(Lb)	<ul style="list-style-type: none"> Red Oak : 1290 Lb  	<ul style="list-style-type: none"> Birch : 1260 Lb 
	<ul style="list-style-type: none"> Hard Maple : 1450 Lb  	<ul style="list-style-type: none"> Walnut : 1010 Lb 