






INTEMPOREL
pre-oiled hardwood floors



GENERAL SPECIFICATIONS

Characteristics		Parquets Alexandra Engineered Lock	
Description	<ul style="list-style-type: none"> • Preoiled engineered floor with locking seal for quick installation 		
Thickness	<ul style="list-style-type: none"> • ± 1/2 in. (12 mm): hardwood veneer of 1/8 inch (3mm) on a 3/8 inch (9mm) plywood 		
Length	<ul style="list-style-type: none"> • Random lengths 12 inches (350 mm) to 78 inches (1.95 m) 		
Widths	<ul style="list-style-type: none"> • 3-7/16 inches (87 mm) and 5-3/16 inches (131 mm) 		
Species	<ul style="list-style-type: none"> • 4 species : Hard Maple, Red Oak, Birch, Walnut 		
Grades	<ul style="list-style-type: none"> • Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots) 		
Colours	<ul style="list-style-type: none"> • 11 colors : Sahara (Except Red Oak), Champagne, Amaretto, Ginger (Hard Maple only), Tan, Truffle, Ardoise, Shadow, Storm, Graphite and Onyx 		
Finish	<ul style="list-style-type: none"> • Vegetable oil naturally impregnated into the wood – available coloured or natural. • Colour (when chosen) created with natural, non-toxic mineral pigments. • Finish mat 5 degree gloss (increases as the floor ages) • 100% ecological and biodegradable oil. • Zero VOC 		
Installation	<ul style="list-style-type: none"> • Floating with an approved underlay/membrane (above grade, on grade or below grade) 		
Subfloor	<ul style="list-style-type: none"> • Wood, concrete or hot water radiant heating systems. 		
Membranes	<ul style="list-style-type: none"> • Finitec : Acousti-Tech™ Premium and Acousti-Tech™ VP 		
Maintenance	<ul style="list-style-type: none"> • Sweep or vacuum regularly to remove dust & grit • Damp mop with warm water as needed • Wood soap : ideally every week • Revitalizer : ideally every 5 washes • Regenerating oil : 2-10 years, depending on the wear 		
Use	<ul style="list-style-type: none"> • Commercial or Residential 		
Accessories	<ul style="list-style-type: none"> • Nosings, Reducers and Vents (Other accessories available on special order) 		
Warranty	<ul style="list-style-type: none"> • Lifetime structural warranty on manufacturing defects • No finish warranty as the oil is in the wood and becomes part of the structure. Only oil issues relating to a manufacturing defect will be considered for warranty purposes. • Parquets Alexandra offers specific maintenance and repair products for our pre-oiled wood and recommends using only these products on our floors. We are not responsible for the use of competitor's products. 		
Packaging		3-7/16 inches (87 mm)	5-3/16 inches (131 mm)
Contents of a box	<ul style="list-style-type: none"> • 34 ft² 	<ul style="list-style-type: none"> • 34 ft² 	
Dimensions of a box	<ul style="list-style-type: none"> • 78-1/16 in L x 11 in W x 3 in H 	<ul style="list-style-type: none"> • 78-1/16 in L x 11 in W x 3 in H 	
Weight of a box	<ul style="list-style-type: none"> • 49 to 53 lb 	<ul style="list-style-type: none"> • 49 to 53 lb 	
Size of a pallet	<ul style="list-style-type: none"> • 40 boxes = 1 360 ft² (4 boxes per Layer x 10 boxes High) 	<ul style="list-style-type: none"> • 40 boxes = 1 360 ft² (4 boxes per Layer x 10 boxes High) 	
Dimensions of a pallet	<ul style="list-style-type: none"> • 86 in L x 38 in W x 35 in H 	<ul style="list-style-type: none"> • 86 in L x 38 in W x 35 in H 	
Hardness of species *			
* As per Janka Hardness scale Force applied in pound(Lb)	<ul style="list-style-type: none"> • Red Oak : 1290 Lb  	<ul style="list-style-type: none"> • Birch : 1260 Lb  	
	<ul style="list-style-type: none"> • Hard Maple : 1450 Lb  	<ul style="list-style-type: none"> • Walnut : 1010 Lb 