

## **MINOR REPAIRS**

## WHAT YOU MUST KNOW

- 1. A REPAIR KIT for each color is available to carry out minor repairs
- 2. The KIT contains a coloured IMPREGNATING OIL pen and FINISHING OIL pen as well as a wax pencil (used primarily for small holes in the surface)
- 3. Small surface scratches can be repaired with just an application of FINISHING OIL apply oil, leave for 5 10 minutes and then wipe off area with a clean cloth
- 1. Sand lightly in the directions of the grain with 100/120 grit sandpaper
- 2. Apply IMPREGNATING OIL to the area to be treated, taking care to delicately blot off the excess oil with a cloth until you have obtained the desired color often using a finger to blend the edges of a repair works better than a cloth. For darker colors, a second application may be necessary. Let dry
- 3. After approximately 12 hours, check with a cloth to see if the color is dry. When dry, apply a fine layer of FINISHING OIL. Take care not to leave any oil on the surface by blotting off the surface with a clean cloth. Let dry completely before judging the final result
- \*\* Do not try to sand an area where you want to correct a color match when the oil is still not dry as it will close the wood pores and 'freeze' the color achieved
- \*\* In the case of a hole to be repaired, use the wax pencil to fill the hole and then use a plastic spatula to remove the surplus wax
- \*\* It is very important to make repairs in the direction of the grain of wood. Let dry completely before judging the final result