



Characteristics	Parquets Alexandra Engineered T-G12 (Tongue & Groove)	
Description	<ul style="list-style-type: none"> • Prefinished Engineered Floor made with hardwood veneer on a 7 layers plywood of Baltic birch 	
Thickness	<ul style="list-style-type: none"> • ± 1/2 in. (12 mm): hardwood veneer of 1/8 inch (3mm) on a 3/8 inch (9mm) plywood 	
Length	<ul style="list-style-type: none"> • Random lengths 12 inches (350 mm) to 78 inches (1.95 m) 	
Widths	<ul style="list-style-type: none"> • 3-1/4 inches (83 mm) and 4-1/2 inches (114 mm) 	
Species	<ul style="list-style-type: none"> • 3 species : Hard Maple, Red Oak, Walnut 	
Grades	<ul style="list-style-type: none"> • Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots) 	
Colors	<ul style="list-style-type: none"> • 16 colors : Pure, Naturel, Latte, Ocean, Urbain, Éclipse, Gunstock, Copper, Coffee, Portobello, Cappuccino, Bronze, Mendes, Barley, Tango, Chocolat 	
Finish	<ul style="list-style-type: none"> • Complete finish system that creates a “thicker” finish that is UV cured. • Wear resistance: superior layer finish based on acrylic and polyurethane with nanoparticles that provides a superior resistance to wear. • Scratch resistance: use of aluminium oxide particles and nanoparticles gives Expression better scratch resistance than most products on the market. • Gloss: semi-gloss (50%) and Satin (30%). Gloss levels are more stable over time because of the resin quality and nanoparticules used in our finish. • Environment : no off-gassing of VOC 	
Installation	<ul style="list-style-type: none"> • Nailed, stapled or glued (at all grades) 	
Subfloor	<ul style="list-style-type: none"> • Wood, concrete or hot water radiant heating systems. 	
Membranes	<ul style="list-style-type: none"> • Finitec : Acousti-Tech™ 7000, 5000, 3500 et Acousti-Tech™ Lead 6, 4.5, 3.3 	
Maintenance	<ul style="list-style-type: none"> • With spray cleaner for prefinished floor 	
Use	<ul style="list-style-type: none"> • Commercial or Residential 	
Accessories	<ul style="list-style-type: none"> • Nosings and Reducers (Other accessories available on special order) 	
Warranty	<ul style="list-style-type: none"> • Lifetime structural warranty on manufacturing defects. • Residential: 35 years Finish warranty. • Commercial: 3 years Finish warranty. 	
Packaging	3-1/4 inches (83 mm)	4-1/2 inches (114 mm)
Contents of a box	<ul style="list-style-type: none"> • 28 ft² 	<ul style="list-style-type: none"> • 30 ft²
Dimensions of a box	<ul style="list-style-type: none"> • 78-1/2 in L x 11 in W x 3 in H 	<ul style="list-style-type: none"> • 78-1/16 in L x 11 in W x 3 in H
Weight of a box	<ul style="list-style-type: none"> • 49 to 53 lb 	<ul style="list-style-type: none"> • 49 to 53 lb
Size of a pallet	<ul style="list-style-type: none"> • 40 boxes = 1 200 ft² (4 boxes per Layer x 10 boxes High) 	<ul style="list-style-type: none"> • 40 boxes = 1 360 ft² (4 boxes per Layer x 10 boxes High)
Dimensions of a pallet	<ul style="list-style-type: none"> • 86 in L x 38 in W x 35 in H 	<ul style="list-style-type: none"> • 86 in L x 38 in W x 35 in H
Hardness of species *		
* As per Janka Hardness scale Force applied in pound(Lb)	<ul style="list-style-type: none"> • Red Oak : 1290 Lb  	<ul style="list-style-type: none"> • Walnut : 1010 Lb 
	<ul style="list-style-type: none"> • Hard Maple : 1450 Lb 