





| Characteristics   | Parquets Alexandra Engineered T-G16 (Tongue & Groove)   |   |
|---|---|---|
| <b>Description</b>  | <ul style="list-style-type: none"> <li>• Prefinished Engineered Floor made of real hardwood plywood on Douglas Fir plywood</li> </ul>   |   |
| <b>Thickness</b>  | <ul style="list-style-type: none"> <li>• ± 5/8 in. (16mm): 3/32 "(2mm) sawn hardwood plywood on 9/16" (14mm) plywood of 5-ply Canadian plywood.</li> </ul>  |   |
| <b>Length</b>   | <ul style="list-style-type: none"> <li>• Random lengths 10 inches (350 mm) to 84 inches (2134 m)</li> </ul>   |   |
| <b>Widths</b>   | <ul style="list-style-type: none"> <li>• 5-3/16 inches (131 mm) and 7-3/16 inches (182 mm)</li> </ul>   |   |
| <b>Species</b>  | <ul style="list-style-type: none"> <li>• 2 species : Hard Maple, Red Oak</li> </ul>   |   |
| <b>Grades</b>   | <ul style="list-style-type: none"> <li>• Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots)</li> </ul>   |   |
| <b>Colors</b>   | <ul style="list-style-type: none"> <li>• 16 colors : Pure, Naturel, Latte, Ocean, Urbain, Éclipse, Gunstock, Copper, Coffee, Portobello, Cappuccino, Bronze, Mendes, Barley, Tango, Chocolat</li> </ul>   |   |
| <b>Finish</b>   | <ul style="list-style-type: none"> <li>• Complete finish system that creates a "thicker" finish that is UV cured.</li> <li>• Wear resistance: superior layer finish based on acrylic and polyurethane with nanoparticles that provides a superior resistance to wear.</li> <li>• Scratch resistance: use of aluminium oxide particles and nanoparticles gives Expression better scratch resistance than most products on the market.</li> <li>• Gloss: semi-gloss (50%) and Satin (30%). Gloss levels are more stable over time because of the resin quality and nanoparticules used in our finish.</li> <li>• Environment : no off-gassing of VOC</li> </ul> |   |
| <b>Installation</b>   | <ul style="list-style-type: none"> <li>• Floating with an approved underlay/membrane (above grade, on grade or below grade)</li> </ul>  |   |
| <b>Subfloor</b>   | <ul style="list-style-type: none"> <li>• Wood, concrete or hot water radiant heating systems.</li> </ul>  |   |
| <b>Membranes</b>  | <ul style="list-style-type: none"> <li>• Finitec : Acousti-Tech™ Premium and Acousti-Tech™ VP</li> </ul>  |   |
| <b>Maintenance</b>  | <ul style="list-style-type: none"> <li>• With spray cleaner for prefinished floor</li> </ul>  |   |
| <b>Use</b>  | <ul style="list-style-type: none"> <li>• Commercial or Residential</li> </ul>   |   |
| <b>Accessories</b>  | <ul style="list-style-type: none"> <li>• Nosings and Reducers (Other accessories available on special order)</li> </ul>   |   |
| <b>Warranty</b>   | <ul style="list-style-type: none"> <li>• Lifetime structural warranty on manufacturing defects.</li> <li>• Residential: 35 years Finish warranty.</li> <li>• Commercial: 3 years Finish warranty.</li> </ul>  |   |
| <b>Packaging</b>  | <b>5-3/16 inches (131 mm)</b>   | <b>7-3/16 inches (182 mm)</b>   |
| <b>Contents of a box</b>                                    | <ul style="list-style-type: none"> <li>• 29 ft<sup>2</sup></li> </ul>   | <ul style="list-style-type: none"> <li>• 20 ft<sup>2</sup></li> </ul>   |
| <b>Dimensions of a box</b>                                  | <ul style="list-style-type: none"> <li>• 84 in L x 11 in W x 3 in H</li> </ul>  | <ul style="list-style-type: none"> <li>• 86 in L x 7.1 in W x 3 in H</li> </ul>   |
| <b>Weight of a box</b>                                      | <ul style="list-style-type: none"> <li>• 58 lb</li> </ul>   | <ul style="list-style-type: none"> <li>• 40 lb</li> </ul>   |
| <b>Size of a pallet</b>                                     | <ul style="list-style-type: none"> <li>• 40 boxes = 1 160 ft<sup>2</sup><br/>(4 boxes per Layer x 10 boxes High)</li> </ul>   | <ul style="list-style-type: none"> <li>• 50 boxes = 1 000 ft<sup>2</sup><br/>(4 boxes per Layer x 10 boxes High)</li> </ul> |
| <b>Dimensions of a pallet</b>                               | <ul style="list-style-type: none"> <li>• 84 in L x 44 in W x 35 in H</li> </ul>   | <ul style="list-style-type: none"> <li>• 86 in L x 36 in W x 35 in H</li> </ul>   |
| <b>Hardness of species *</b>                                |   |   |
| * As per Janka Hardness scale<br>Force applied in pound(Lb) | <ul style="list-style-type: none"> <li>• Red Oak : 1290 Lb </li> </ul>  |   |
|   | <ul style="list-style-type: none"> <li>• Hard Maple : 1450 Lb </li> </ul>   |   |