





GENERAL SPECIFICATIONS

EXPRESSION
VARNISHED FLOORS

Characteristics	Parquets Alexandra Engineered T-G19 (Tongue & Groove)	
Description	<ul style="list-style-type: none"> • Prefinished Engineered Floor (19mm) thick, consisting of 5/32" (4mm) of hardwood on substrate made of 1/2" (13mm) quarter cut softwood strips and a backing 3/32 "(2mm). 	
Thickness	<ul style="list-style-type: none"> • ± 3/4 in (19mm) 	
Length	<ul style="list-style-type: none"> • Random lengths 10 inches (350 mm) to 84 inches (2134 m) 	
Widths	<ul style="list-style-type: none"> • 5-1/8 inches (130 mm) and 7-1/8 inches (181 mm) 	
Species	<ul style="list-style-type: none"> • 2 species : Hard Maple, Red Oak 	
Grades	<ul style="list-style-type: none"> • Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots) 	
Colors	<ul style="list-style-type: none"> • 16 colors : Pure, Naturel, Latte, Ocean, Urbain, Éclipse, Gunstock, Copper, Coffee, Portobello, Cappuccino, Bronze, Mendes, Barley, Tango, Chocolat 	
Finish	<ul style="list-style-type: none"> • Complete finish system that creates a "thicker" finish that is UV cured. • Wear resistance: superior layer finish based on acrylic and polyurethane with nanoparticles that provides a superior resistance to wear. • Scratch resistance: use of aluminium oxide particles and nanoparticles gives Expression better scratch resistance than most products on the market. • Gloss: semi-gloss (50%) and Satin (30%). Gloss levels are more stable over time because of the resin quality and nanoparticules used in our finish. • Environment : no off-gassing of VOC 	
Installation	<ul style="list-style-type: none"> • Floating with an approved underlay/membrane (above grade, on grade or below grade) 	
Subfloor	<ul style="list-style-type: none"> • Wood, concrete or hot water radiant heating systems. 	
Membranes	<ul style="list-style-type: none"> • Finitec : Acousti-Tech™ Premium and Acousti-Tech™ VP 	
Maintenance	<ul style="list-style-type: none"> • With spray cleaner for prefinished floor 	
Use	<ul style="list-style-type: none"> • Commercial or Residential 	
Accessories	<ul style="list-style-type: none"> • Nosings and Reducers (Other accessories available on special order) 	
Warranty	<ul style="list-style-type: none"> • Lifetime structural warranty on manufacturing defects. • Residential: 35 years Finish warranty. • Commercial: 3 years Finish warranty. 	
Packaging	5-1/8 inches (130 mm)	7-1/8 inches (181 mm)
Contents of a box	<ul style="list-style-type: none"> • 23 ft² 	<ul style="list-style-type: none"> • 20 ft²
Dimensions of a box	<ul style="list-style-type: none"> • 84 in L x 11 in W x 3 in H 	<ul style="list-style-type: none"> • 86 in L x 7.1 in W x 3 in H
Weight of a box	<ul style="list-style-type: none"> • 50 lb 	<ul style="list-style-type: none"> • 43 lb
Size of a pallet	<ul style="list-style-type: none"> • 40 boxes = 1 160 ft² (4 boxes per Layer x 10 boxes High) 	<ul style="list-style-type: none"> • 50 boxes = 1 000 ft² (4 boxes per Layer x 10 boxes High)
Dimensions of a pallet	<ul style="list-style-type: none"> • 84 in L x 44 in W x 35 in H 	<ul style="list-style-type: none"> • 86 in L x 36 in W x 35 in H
Hardness of species *	<ul style="list-style-type: none"> • Red Oak : 1290 Lb  • Hard Maple : 1450 Lb  	
* As per Janka Hardness scale Force applied in pound(Lb)		