




GENERAL SPECIFICATIONS

Characteristics		Parquets Alexandra Engineered T-G12 (Tongue & Groove)	
Description	<ul style="list-style-type: none"> Prefinished Engineered Floor made with hardwood veneer on a 7 layers plywood of Baltic birch 		
Thickness	<ul style="list-style-type: none"> ± 1/2 in. (12 mm): hardwood veneer of 1/8 inch (3mm) on a 3/8 inch (9mm) plywood 		
Length	<ul style="list-style-type: none"> Random lengths 12 inches (350 mm) to 78 inches (1.95 m) 		
Widths	<ul style="list-style-type: none"> 3-1/4 inches (83 mm) and 4-1/2 inches (114 mm) 		
Species	<ul style="list-style-type: none"> 2 species : Hard Maple, Red Oak 		
Grades	<ul style="list-style-type: none"> Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots) 		
Colors	<ul style="list-style-type: none"> 5 colors : Carat, Voilà!, Noble, Rebel and Alaska 		
Finish	<ul style="list-style-type: none"> Complete finish system that creates a “thicker” finish that is UV cured. 		
	<ul style="list-style-type: none"> Wear resistance: superior layer finish based on acrylic and polyurethane with nanoparticles that provides a superior resistance to wear. 		
	<ul style="list-style-type: none"> Scratch resistance: use of aluminium oxide particles and nanoparticles gives Expression better scratch resistance than most products on the market. 		
	<ul style="list-style-type: none"> Gloss: Matte (15%). Stable gloss in the time because of the resin quality used and the nanoparticles. 		
	<ul style="list-style-type: none"> Environment : no off-gassing of VOC 		
Installation	<ul style="list-style-type: none"> Nailed, stapled or glued (at all grades) 		
Subfloor	<ul style="list-style-type: none"> Wood, concrete or hot water radiant heating systems. 		
Membranes	<ul style="list-style-type: none"> Finitec : Acousti-Tech™ 7000, 5000, 3500 et Acousti-Tech™ Lead 6, 4.5, 3.3 		
Maintenance	<ul style="list-style-type: none"> With spray cleaner for prefinished floor 		
Use	<ul style="list-style-type: none"> Commercial or Residential 		
Accessories	<ul style="list-style-type: none"> Nosings and Reducers (Other accessories available on special order) 		
Warranty	<ul style="list-style-type: none"> Lifetime structural warranty on manufacturing defects. 		
	<ul style="list-style-type: none"> Residential: 35 years Finish warranty. 		
	<ul style="list-style-type: none"> Commercial: 3 years Finish warranty. 		
Packaging	3-1/4 inches (83 mm)	4-1/2 inches (114 mm)	
Contents of a box	<ul style="list-style-type: none"> 30 ft² 	<ul style="list-style-type: none"> 34 ft² 	
Dimensions of a box	<ul style="list-style-type: none"> 78-1/16 in L x 11 in W x 3 in H 	<ul style="list-style-type: none"> 78-1/16 in L x 11 in W x 3 in H 	
Weight of a box	<ul style="list-style-type: none"> 49 to 53 lb 	<ul style="list-style-type: none"> 49 to 53 lb 	
Size of a pallet	<ul style="list-style-type: none"> 40 boxes = 1 200 ft² (4 boxes per Layer x 10 boxes High) 	<ul style="list-style-type: none"> 40 boxes = 1 360 ft² (4 boxes per Layer x 10 boxes High) 	
Dimensions of a pallet	<ul style="list-style-type: none"> 86 in L x 38 in W x 35 in H 	<ul style="list-style-type: none"> 86 in L x 38 in W x 35 in H 	
Hardness of species *			
* As per Janka Hardness scale Force applied in pound(Lb)	<ul style="list-style-type: none"> Red Oak : 1290 Lb 		
	<ul style="list-style-type: none"> Hard Maple : 1450 Lb 