




Characteristics		Parquets Alexandra Engineered T-G16 (Tongue & Groove)	
Description	<ul style="list-style-type: none"> • Prefinished Engineered Floor made of real hardwood plywood on Douglas Fir plywood 		
Thickness	<ul style="list-style-type: none"> • ± 5/8 in. (16mm): 3/32 "(2mm) sawn hardwood plywood on 9/16" (14mm) plywood of 5-ply Canadian plywood. 		
Length	<ul style="list-style-type: none"> • Random lengths 10 inches (254 mm) to 84 inches (2134 mm) 		
Widths	<ul style="list-style-type: none"> • 5-3/16 inches (131 mm) and 7-3/16 inches (182 mm) 		
Species	<ul style="list-style-type: none"> • 2 species : Hard Maple, Red Oak 		
Grades	<ul style="list-style-type: none"> • Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots) 		
Colors	<ul style="list-style-type: none"> • 5 colors : Carat, Voilà!, Noble, Rebel and Alaska 		
Finish	<ul style="list-style-type: none"> • Complete finish system that creates a “thicker” finish that is UV cured. 		
	<ul style="list-style-type: none"> • Wear resistance: superior layer finish based on acrylic and polyurethane with nanoparticles that provides a superior resistance to wear. 		
	<ul style="list-style-type: none"> • Scratch resistance: use of aluminium oxide particles and nanoparticles gives Expression better scratch resistance than most products on the market. 		
	<ul style="list-style-type: none"> • Gloss: Matte (15%). Stable gloss in the time because of the resin quality used and the nanoparticles. 		
	<ul style="list-style-type: none"> • Environment : no off-gassing of VOC 		
Installation	<ul style="list-style-type: none"> • Nailed, stapled or glued (at all grades) 		
Subfloor	<ul style="list-style-type: none"> • Wood, concrete or hot water radiant heating systems. 		
Membranes	<ul style="list-style-type: none"> • Finitec : Acousti-Tech™ 7000, 5000, 3500 et Acousti-Tech™ Lead 6, 4.5, 3.3 		
Maintenance	<ul style="list-style-type: none"> • With spray cleaner for prefinished floor 		
Use	<ul style="list-style-type: none"> • Commercial or Residential 		
Accessories	<ul style="list-style-type: none"> • Nosings and Reducers (Other accessories available on special order) 		
Warranty	<ul style="list-style-type: none"> • Lifetime structural warranty on manufacturing defects. • Residential: 35 years Finish warranty. • Commercial: 3 years Finish warranty. 		
Packaging		5-3/16 inches (131 mm)	7-3/16 inches (182 mm)
Contents of a box	<ul style="list-style-type: none"> • 29 ft² 	<ul style="list-style-type: none"> • 20 ft² 	
Dimensions of a box	<ul style="list-style-type: none"> • 84 in L x 11 in W x 3 in H 	<ul style="list-style-type: none"> • 86 in L x 7.1 in W x 3 in H 	
Weight of a box	<ul style="list-style-type: none"> • 58 lb 	<ul style="list-style-type: none"> • 40 lbs 	
Size of a pallet	<ul style="list-style-type: none"> • 40 boxes = 1 160 ft² 	<ul style="list-style-type: none"> • 50 boxes = 1000 ft² 	
Dimensions of a pallet	<ul style="list-style-type: none"> • 86 in L x 38 in W x 35 in H 	<ul style="list-style-type: none"> • 86 in L x 38 in W x 35 in H 	
Hardness of species *			
* As per Janka Hardness scale Force applied in pound(Lb)	<ul style="list-style-type: none"> • Red Oak : 1290 Lb  		
	<ul style="list-style-type: none"> • Hard Maple : 1450 Lb 