


GENERAL SPECIFICATIONS

Characteristics		Parquets Alexandra Engineered T-G19 (Tongue & Groove)	
Description	<ul style="list-style-type: none"> Prefinished Engineered Floor (19mm) thick, consisting of 5/32" (4mm) of hardwood on substrate made of 1/2" (13mm) quarter cut softwood strips and a backing 3/32" (2mm). 		
Thickness	<ul style="list-style-type: none"> ± 3/4 in (19mm) 		
Length	<ul style="list-style-type: none"> Random lengths 10 inches (254 mm) to 84 inches (2134 mm) 		
Widths	<ul style="list-style-type: none"> 5-1/8 inches (130 mm) and 7-1/8 inches (181 mm) 		
Species	<ul style="list-style-type: none"> 2 species : Hard Maple, Red Oak 		
Grades	<ul style="list-style-type: none"> Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots) 		
Colors	<ul style="list-style-type: none"> 5 colors : Carat, Voilà!, Noble, Rebel and Alaska 		
Finish	<ul style="list-style-type: none"> Complete finish system that creates a "thicker" finish that is UV cured. 		
	<ul style="list-style-type: none"> Wear resistance: superior layer finish based on acrylic and polyurethane with nanoparticles that provides a superior resistance to wear. 		
	<ul style="list-style-type: none"> Scratch resistance: use of aluminium oxide particles and nanoparticles gives Expression better scratch resistance than most products on the market. 		
	<ul style="list-style-type: none"> Gloss: Matte (15%). Stable gloss in the time because of the resin quality used and the nanoparticles. 		
	<ul style="list-style-type: none"> Environment : no off-gassing of VOC 		
Installation	<ul style="list-style-type: none"> Nailed, stapled or glued (at all grades) 		
Subfloor	<ul style="list-style-type: none"> Wood, concrete or hot water radiant heating systems. 		
Membranes	<ul style="list-style-type: none"> Finitec : Acousti-Tech™ 7000, 5000, 3500 et Acousti-Tech™ Lead 6, 4.5, 3.3 		
Maintenance	<ul style="list-style-type: none"> With spray cleaner for prefinished floor 		
Use	<ul style="list-style-type: none"> Commercial or Residential 		
Accessories	<ul style="list-style-type: none"> Nosings and Reducers (Other accessories available on special order) 		
Warranty	<ul style="list-style-type: none"> Lifetime structural warranty on manufacturing defects. 		
	<ul style="list-style-type: none"> Residential: 35 years Finish warranty. 		
	<ul style="list-style-type: none"> Commercial: 3 years Finish warranty. 		
Packaging		5-1/8 inches (130 mm)	7-1/8 inches (181 mm)
Contents of a box	<ul style="list-style-type: none"> 23 ft² 	<ul style="list-style-type: none"> 16 ft² 	
Dimensions of a box	<ul style="list-style-type: none"> 84 in L x 11 in W x 3 in H 	<ul style="list-style-type: none"> 86 in L x 7.1 in W x 3 in H 	
Weight of a box	<ul style="list-style-type: none"> 58 lb 	<ul style="list-style-type: none"> 40 lbs 	
Size of a pallet	<ul style="list-style-type: none"> 40 boxes = 1 160 ft² 	<ul style="list-style-type: none"> 50 boxes = 1000 ft² 	
Dimensions of a pallet	<ul style="list-style-type: none"> 86 in L x 38 in W x 35 in H 	<ul style="list-style-type: none"> 86 in L x 38 in W x 35 in H 	
Hardness of species *			
* As per Janka Hardness scale Force applied in pound(Lb)	<ul style="list-style-type: none"> Red Oak : 1290 Lb  		
	<ul style="list-style-type: none"> Hard Maple : 1450 Lb 