





GENERAL SPECIFICATIONS

SIGNATURE
OILED FLOORS

Characteristics		Parquets Alexandra Engineered T-G12 (Tongue & Groove)
Description		• Preoiled Engineered Floor made with hardwood veneer on a 7 layers plywood of Baltic birch
Thickness		• ± 1/2 in. (12 mm): hardwood veneer of 1/8 inch (3mm) on a 3/8 inch (9mm) plywood
Length		• Random lengths 12 inches (350 mm) to 78 inches (1.95 m)
Widths		• 3-1/4 inches (83 mm) and 4-1/2 inches (114 mm)
Species		• 3 species : Hard Maple, Red Oak, Walnut
Grades		• Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots)
Colours		• 15 colors : Versailles, Sahara, Champagne, Amaretto, Ginger (Hard Maple only), Tan, Truffle, Ardoise, Mojave, Himalaya, Shadow, Storm, Seagray, Graphite et Onyx
Finish		<ul style="list-style-type: none"> • Vegetable oil naturally impregnated into the wood – available coloured or natural. • Colour (when chosen) created with natural, non-toxic mineral pigments. • Finish mat 5 degree gloss (increases as the floor ages) • 100% ecological and biodegradable oil. • Zero VOC
Installation		• Nailed, stapled or glued (at all grades)
Subfloor		• Wood, concrete or hot water radiant heating systems.
Membranes		• Finitec : Acousti-Tech™ 7000, 5000, 3500 et Acousti-Tech™ Lead 6, 4.5, 3.3
Maintenance		<ul style="list-style-type: none"> • Sweep or vacuum regularly to remove dust & grit • Damp mop with warm water as needed • Wood soap : ideally every week • Revitalizer : ideally every 4 washes • Regenerating oil : 2-10 years, depending on the wear
Use		• Commercial or Residential
Accessories		• Nosings, Reducers and Vents (Other accessories available on special order)
Warranty		<ul style="list-style-type: none"> • Lifetime structural warranty on manufacturing defects • No finish warranty as the oil is in the wood and becomes part of the structure. Only oil issues relating to a manufacturing defect will be considered for warranty purposes. • Parquets Alexandra offers specific maintenance and repair products for our pre-oiled wood and recommends using only these products on our floors. We are not responsible for the use of competitor's products.

Packaging	3-1/4 inches (83 mm)	4-1/2 inches (114 mm)
Contents of a box	• 28 ft ²	• 30 ft ²
Dimensions of a box	• 78-1/16 in L x 11 in W x 3 in H	• 78-1/16 in L x 11 in W x 3 in H
Weight of a box	• 49 to 53 lb	• 49 to 53 lb
Size of a pallet	• 40 boxes = 1 200 ft ² (4 boxes per Layer x 10 boxes High)	• 40 boxes = 1 360 ft ² (4 boxes per Layer x 10 boxes High)
Dimensions of a pallet	• 86 in L x 38 in W x 35 in H	• 86 in L x 38 in W x 35 in H
Hardness of species *		
* As per Janka Hardness Scale Force applied in pound(Lb)	• Red Oak : 1290 Lb 	• Walnut : 1010 Lb 
	• Hard Maple : 1450 Lb 