




GENERAL SPECIFICATIONS

SIGNATURE
OILED FLOORS

Characteristics		Parquets Alexandra Engineered T-G16 (Tongue & Groove)	
Description	<ul style="list-style-type: none"> Preoiled Engineered Floor made of real hardwood plywood on Douglas Fir plywood 		
Thickness	<ul style="list-style-type: none"> ± 5/8 in. (16 mm): 3/32 "(2mm) sawn hardwood plywood on 9/16" (14mm) plywood of 5-ply Canadian plywood. 		
Length	<ul style="list-style-type: none"> Random lengths 10 inches (254 mm) to 84 inches (2134 mm) 		
Widths	<ul style="list-style-type: none"> 5-3/16 inches (131 mm) and 7-3/16 inches (182 mm) 		
Species	<ul style="list-style-type: none"> 2 species : Hard Maple, Red Oak 		
Grades	<ul style="list-style-type: none"> Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots) 		
Colours	<ul style="list-style-type: none"> 15 colors : Versailles, Sahara, Champagne, Amaretto, Ginger (Hard Maple only), Tan, Truffle, Ardoise, Mojave, Himalaya, Shadow, Storm, Seagray, Graphite et Onyx 		
Finish	<ul style="list-style-type: none"> Vegetable oil naturally impregnated into the wood – available coloured or natural. Colour (when chosen) created with natural, non-toxic mineral pigments. Finish mat 5 degree gloss (increases as the floor ages) 100% ecological and biodegradable oil. Zero VOC 		
Installation	<ul style="list-style-type: none"> Nailed, stapled or glued (at all grades) 		
Subfloor	<ul style="list-style-type: none"> Wood, concrete or hot water radiant heating systems. 		
Membranes	<ul style="list-style-type: none"> Finitec : Acousti-Tech™ 7000, 5000, 3500 et Acousti-Tech™ Lead 6, 4.5, 3.3 		
Maintenance	<ul style="list-style-type: none"> Sweep or vacuum regularly to remove dust & grit Damp mop with warm water as needed Wood soap : ideally every week Revitalizer : ideally every 4 washes Regenerating oil : 2-10 years, depending on the wear 		
Use	<ul style="list-style-type: none"> Commercial or Residential 		
Accessories	<ul style="list-style-type: none"> Nosings, Reducers and Vents (Other accessories available on special order) 		
Warranty	<ul style="list-style-type: none"> Lifetime structural warranty on manufacturing defects No finish warranty as the oil is in the wood and becomes part of the structure. Only oil issues relating to a manufacturing defect will be considered for warranty purposes. Parquets Alexandra offers specific maintenance and repair products for our pre-oiled wood and recommends using only these products on our floors. We are not responsible for the use of competitor's products. 		
Packaging		5-3/16 inches (131 mm)	7-3/16 inches (182 mm)
Contents of a box	<ul style="list-style-type: none"> 29 ft² 	<ul style="list-style-type: none"> 20 ft² 	
Dimensions of a box	<ul style="list-style-type: none"> 84 in L x 11 in W x 3 in H 	<ul style="list-style-type: none"> 86 in L x 7.1 in W x 3 in H 	
Weight of a box	<ul style="list-style-type: none"> 58 lb 	<ul style="list-style-type: none"> 40 lb 	
Size of a pallet	<ul style="list-style-type: none"> 40 boxes = 1 160 ft² (4 boxes per Layer x 10 boxes High) 	<ul style="list-style-type: none"> 50 boxes = 1 000 ft² (5 boxes per Layer x 10 boxes High) 	
Dimensions of a pallet	<ul style="list-style-type: none"> 86 in L x 44 in W x 35 in H 	<ul style="list-style-type: none"> 86 in L x 36 in W x 35 in H 	
Hardness of species *			
* As per Janka Hardness Scale Force applied in pound(Lb)	<ul style="list-style-type: none"> Red Oak : 1290 Lb  		
	<ul style="list-style-type: none"> Hard Maple : 1450 Lb 