




GENERAL SPECIFICATIONS

SIGNATURE
OILED FLOORS



Characteristics		Parquets Alexandra Engineered T-G19 (Tongue & Groove)	
Description	<ul style="list-style-type: none"> • Preoiled Engineered Floor (19mm) thick, consisting of 5/32" (4mm) of hardwood on substrate made of 1/2" (13mm) quarter cut softwood strips and a backing 3/32" (2mm). 		
Thickness	<ul style="list-style-type: none"> • ± 3/4 in. (19 mm) 		
Length	<ul style="list-style-type: none"> • Random lengths 10 inches (254 mm) to 84 inches (2134 mm) 		
Widths	<ul style="list-style-type: none"> • 5-1/8 inches (130 mm) and 7-1/8 inches (181 mm) 		
Species	<ul style="list-style-type: none"> • 2 species : Hard Maple, Red Oak 		
Grades	<ul style="list-style-type: none"> • Distinct (Natural mix of heartwood and sapwood – has colour variation – no knots) 		
Colours	<ul style="list-style-type: none"> • 15 colors : Versailles, Sahara, Champagne, Amaretto, Ginger (Hard Maple only), Tan, Truffle, Ardoise, Mojave, Himalaya, Shadow, Storm, Seagray, Graphite et Onyx 		
Finish	<ul style="list-style-type: none"> • Vegetable oil naturally impregnated into the wood – available coloured or natural. • Colour (when chosen) created with natural, non-toxic mineral pigments. • Finish mat 5 degree gloss (increases as the floor ages) • 100% ecological and biodegradable oil. • Zero VOC 		
Installation	<ul style="list-style-type: none"> • Nailed, stapled or glued (at all grades) 		
Subfloor	<ul style="list-style-type: none"> • Wood, concrete or hot water radiant heating systems. 		
Membranes	<ul style="list-style-type: none"> • Finitec : Acousti-Tech™ 7000, 5000, 3500 et Acousti-Tech™ Lead 6, 4.5, 3.3 		
Maintenance	<ul style="list-style-type: none"> • Sweep or vacuum regularly to remove dust & grit • Damp mop with warm water as needed • Wood soap : ideally every week • Revitalizer : ideally every 4 washes • Regenerating oil : 2-10 years, depending on the wear 		
Use	<ul style="list-style-type: none"> • Commercial or Residential 		
Accessories	<ul style="list-style-type: none"> • Nosings, Reducers and Vents (Other accessories available on special order) 		
Warranty	<ul style="list-style-type: none"> • Lifetime structural warranty on manufacturing defects • No finish warranty as the oil is in the wood and becomes part of the structure. Only oil issues relating to a manufacturing defect will be considered for warranty purposes. • Parquets Alexandra offers specific maintenance and repair products for our pre-oiled wood and recommends using only these products on our floors. We are not responsible for the use of competitor's products. 		
Packaging	5-1/8 inches (130 mm)		7-1/8 inches (181 mm)
Contents of a box	<ul style="list-style-type: none"> • 23 ft² 		<ul style="list-style-type: none"> • 16 ft²
Dimensions of a box	<ul style="list-style-type: none"> • 84 in L x 11 in W x 3 in H 		<ul style="list-style-type: none"> • 86 in L x 7.1 in W x 3 in H
Weight of a box	<ul style="list-style-type: none"> • 50 lb 		<ul style="list-style-type: none"> • 43 lb
Size of a pallet	<ul style="list-style-type: none"> • 40 boxes = 1 160 ft² (4 boxes per Layer x 10 boxes High) 		<ul style="list-style-type: none"> • 50 boxes = 1 000 ft² (5 boxes per Layer x 10 boxes High)
Dimensions of a pallet	<ul style="list-style-type: none"> • 86 in L x 44 in W x 35 in H 		<ul style="list-style-type: none"> • 86 in L x 36 in W x 35 in H
Hardness of species *			
* As per Janka Hardness Scale Force applied in pound(Lb)	<ul style="list-style-type: none"> • Red Oak : 1290 Lb  		
	<ul style="list-style-type: none"> • Hard Maple : 1450 Lb 