

## MINOR REPAIRS

### WHAT YOU MUST KNOW

1. A REPAIR KIT for each color is available to carry out minor repairs
  2. The KIT contains a coloured IMPREGNATING OIL pen and FINISHING OIL pen as well as a wax pencil (used primarily for small holes in the surface)
  3. Small surface scratches can be repaired with just an application of FINISHING OIL – apply oil, leave for 5 – 10 minutes and then wipe off area with a clean cloth
- 

1. Sand lightly in the directions of the grain with 120 grit sandpaper
2. Apply IMPREGNATING OIL to the area to be treated, taking care to delicately blot off the excess oil with a cloth until you have obtained the desired color - often using a finger to blend the edges of a repair works better than a cloth. For darker colors, a second application may be necessary. Let dry
3. After approximately 12 hours, check with a cloth to see if the color is dry. When dry apply a fine layer of FINISHING OIL. Take care not to leave any oil on the surface by blotting off the surface with a clean cloth. Let dry completely before judging the final result

\* Do not try to sand an area where you want to correct a color match when the oil is still not dry as it will close the wood pores and ‘freeze’ the color achieved

\*\* In the case of a hole to be repaired, use the wax pencil to fill the hole and then use a plastic spatula to remove the excess wax

\*\*\* It is very important to make repairs in the direction of the grain of wood. Let dry completely before judging the final result